



GV8 type gauge valve is a block and bleed needle pattern gauge valve with specially designed integral bleed of M8. Ideal for use on applications requiring bleeding or venting of media. Self centering needle non-rotating, on the valve seat. The conical metal tip (stem type CT) press fitted ensures perfect alignment for positive bubble tight shut-off. Standard end connections are male inlet and female outlet or female inlet and female outlet from 1/4" to 3/4".

Applications

- Installation of instrument and gauge
- isolation of Instrument
- Venting of Instrument
- Liquid and vapor service



GOST

CE

Technical specifications

Design Pressure	: 6000 PSI
Max temp.	: 240°C
Material	: Stainless Steel
Stem	: (CT) Conical tip
Gland Packing	: PTFE
Stem packing area	: Burnished finish for smooth valve operation
Safety Feature	: Back seating for Preventing stem blowout




Size	Type	Body dimensions		Height (open) C	Handle D	Handle OD E
		A	B			
1/4"	FxF	32	32	63	40	10
	MxF	48	32	63	40	10
	MxM	48	48	63	40	10
3/8"	FxF	32	32	63	40	10
	MxF	48	32	63	40	10
	MxM	48	48	63	40	10
1/2"	FxF	50	50	95.5	55	12.7
	MxF	70	50	95.5	55	12.7
	MxM	70	70	95.5	55	12.7
3/4"	FxF	75	38	86.6	55	12.7
	MxF	83	38	86.6	55	12.7
	MxM	88	38	86.6	55	12.7

All dimensions are in mm.

Optional:

GV 10 - High pressure valves for 10,000 psi pressure
GV 20 - High pressure valves for 20,000 psi pressure

Note : Other combination sizes available on request.
Please contact us for more details.



Notes : • Drawings are not to scale.
• All Dimensions are in mm.

How To Order

Body Material	Stem Packing	Size = P x P1	Connections (inlet x outlet)	Threads
C = Carbon Steel	P = PTFE	24 = 1/4" x 1/4"	FF = Female x Female	N = NPT (ANSI B 1.20.1)
S = SS 316	G = Grafoil	33 = 3/8" x 3/8"	MF = Male x Female	P = BSPP (BS 2779, ISO 228/1)
S4 = SS 304		44 = 1/2" x 1/2"	MM = Male x Male	B = BSPT (BS 21, ISO 7/1)
SL = SS 316L		46 = 1/2" x 3/4"	SW = Socket Weld	
M4 = Monel 400		64 = 3/4" x 1/2"		
M5 = Monel 500		66 = 3/4" x 3/4"		
H = Hastelloy C				
B = Brass				

Options

TF : Compliance to NACE standard
SG : For Oxygen service, valves are supplied cleaned, degreased and suitably packed.
GH : Material test certificate
GO : Hydro test certificate
D4 : 1/4" NPT (M) Drain Plug instead of M8 bleed
BLD4 : Bleeder 1/4" NPT (Male)

* Material test certificate will be provided for wetted parts only with chemical composition testing. For others, please consult factory.

Example

To place an order simply refer to the codes in the table.

Valve Type : Body Material + Stem Packing + Size + Connections + Threads + Options

GV8 + S + P + 44 + MF + N = GV8 . S . P . 44 . MF . N . Options

Standard Valve Materials

Valve	Body	Bonnet	Stem	Tip
Carbon Steel	CS A105	CS A105	SS 304	SS 304
Stainless Steel	SS 316	SS 316	SS 316	SS 316
Monel	Monel	Monel	Monel	Monel

Note : Specifications and dimensions given in this product catalogue represents the state of engineering at the time of printing.
 Modifications may take place and materials specified may be replaced by others without prior notice.